



MER'S MARK + PRODUCTION DATE MOULD NR. + DOT CODE

INDEX ZMENY / modifications	DATE	REVISION	SOUHLAS TECHNODOGA		DATE	VIS	TEPIUDA PLENEN Filling temperature	≤ 20 °C	NOMINAL OBJEM Capacity fillpoint	ml ± ml	POTZNAVKA Remarks	
B Form Nr. and Def. code reposition, H-I-ol. increased	23.108	Zap. Pam.	SOUHYBATYVNI VYRZMUDI	DATE	VIS	TEPIUDA ZPRAVDYVNI Conditioning temperature	≤ 95 °C	TOTAL OBJEM Capacity brandl	720 ml ± 15 ml	ZAKAZNIK Customer		
C Rename	14.3.17		VYRZMUDI	DATE	VIS	OBSAH CO ₂ CO ₂ content	≤ g/l	HNOJNOST Average glass weight	305 g	PODOBNY JAKO Similar to		
			FS SOUHLAS FS approved	VYRZMUDI	DATE	OBSAH ALKOHOLU Alcohol content	≤ Vol%	STREDNI TLOUSTKA STENY Average wall thickness	2.74 mm	NARAZUJE Replace No		
			NETOLROVANE ROZMERY DLE DIN 6129 dimensions without tolerances conform to standard DIN 6129				AXIALNI ZATIZEN Axial pressure	100 daN	PROBER POUJ USTIM Neck connection dia	75 mm	POTZNAVKA CSLO	
						POUZITI Disposal	MW	AW	EW	X	WITRNI PROBER KALIBRU In through bore	
						PROCES Process	BB	PB	XPB	X	BARVA Color	WE
											KRESLIL Dra	Pam
											DATE	14.03.17
											DMA Typ	AZ
											Item No	5N015 0720 6064

vetropack

Vetropack Moravia Glass a.s.
CZ-69701 Kyjov
Tel: 00420-518 603 111
www.vetropack.com

POZNAVKA
Designation
FACETA 305g 1082RH 720ml
JF FACETI 305