



Bottom view

Producer + Year production

Dot code + Mould number

INDEX	ZNENY / modifications	DAT	JMENO	PT approved	SOULAS TECHNOLOGA	DAT	VIS	TEPIJDA PLINEN	Filing temperature	≤	15 °C	NOMINAL OBJEM	Capacity filloport	1000 ml ±	ml	POZNAMKA	Remarks
B	Zmena umistení roku výroby	10.11.11	Kop	Pom	SOULAS VYRZMOV	DAT	VIS	TEPIJDA, ZPRAVOKAM	Conditioning temperature	≤	°C	TOTAL OBJEM	Capacity brutto	1035 ml ± 10 ml		ZAKAZNIK	Customer
C	Renome	28.05.15			VIRZMOV	DAT	VIS	OBSAH CO <sub>2</sub>	CO <sub>2</sub> content	≤	g/l	HMOJNOST	Approx. glass weight	515 g		PODOBNY JAKO	Similar to
					VYRZMOV	DAT	VIS	OBSAH ALKOHOLU	Alcohol content	≤	Va%	STREDNI TLUSTIKA STENY	Average wall thickness	3,22 mm		NAHRAZUJE	Replaces No.
								AXIALNI ZATIZEN	Axial pressure		ddN	PROKER POU USTIM	Neck connection dia	25 mm		NABIDKA CSLO	Offer No.
								POUZITI	Disposal	MW	AW	WITRIN PROKER KALIBRU	Inn. through bore	16 mm		11	ESPO304.1000.354.7_A
								PROCES	Process	BB	PB	BARVA	Color	BR		DMA Typ	File/typ
										X						AZ	28.05.15

NETOBEROVANE ROZMERY  
DLE DIN 6129  
dimensions without tolerances  
conform to standard DIN 6129

POZNAMKA  
Designation  
VYROBEK CSLO  
Item No.  
LEKOYKA 515g PP2815 1000ml  
CP LEKOYKA 515

Vetropack  
Moravia Glass a.s.  
CZ-69701, Kyjov  
Tel. 00420-518 603 111  
www.vetropack.com

VMM-0701-01-FOR-006-CZ/EN