

INDEX	PROJEKTNE / modifications	DATE	NAME
B	uskidelen naips na dnu sa postrojecom stanjnjem	20.04.10	HS
C	promjena naziva artikla	04.04.19	HS

NETOLERANJE MJERE PERMA DIN 679 dimensions without tolerances conform to standard DIN 679	PT DOOBREN PT approved	DATE	VIS
	PIP DOOBREN PIB released	04.04.19	04.04.19
FS DOOBREN FS approved	STAKLANA VST	DATE	VIS
	04.04.19	04.04.19	04.04.19

PRITISAK ZATVARANJA Avalt pressure	100 daN	
	PROMIER VRATA Need connection dia	27,5 mm
	MIN. PROLAZ KRIZ VRTA Min through bore	18 mm

TEMP. PUNJENJA Filling temperature	≤ 15 °C
TEMPERATURA OSUŠAKE Conditioning temperature	≤ °C
SADRŽAJ CO ₂ CO ₂ content	≤ g/l
SADRŽAJ ALKOHOLA Alcohol content	≤ 4,5 vol%
PROSJECA DEBLJINA STIENKE Average wall thickness	3,98 mm
TEŽINA Approx. glass weight	675 g

NAZIVNI SADRŽAJ Capacity fillpoint	700 ml ± 10 ml
SADRŽAJ DO VRHA Capacity brimful	715 ml ± ml
KUPAK Customer	Standard

NAPOVEDNA Remarks	
MIJENJA Scale	1:1
PROJUDA BROJ Order No	E655604.0700.354.3.B
MIJENJA BR Replace No	65122.0700.354.3.B

TIPOVAZ Filetype	AZ
BR. ARTIKLA Item No	65122.0700.354.3

MAZIV ARTIKLA Designation	Cutura 675g PP3121 700ml
BR. ARTIKLA Item No	65122.0700.354.3

